



PRODUCT INFORMATION

Mod. R&S. 05/0

Pag. 1/1

Last Updating: 10/2008

SUBLISTOP

Description

Heat seal material for Cad-Cut[®] applications on dyed garments (sublimation inks).

The special formulation and processing of the material create a barrier to the dyes of the textile avoiding the sublimation bleed: decoration colour won't change along time.

Polyester backing.

Basic Information

Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:

Temperature: 165°C

Time: 15"

Pressure: min.

Application Instructions

- 1) Cut the material **in reverse**
- 2) Weed the exceeding material
- 3) Place the material on the garment with its polyester support
- 4) Heat apply
- 5) Remove polyester backing once **cold**

Suitable for

Polyester fabrics dyed with sublimation inks

Washing: (wait 24h after the heat transfer)

30°C Max. – do not use bleach or other aggressive chemical agents

Dry-cleaning : no

Tumble drier : yes

N.B. : all information given in this sheet are based on our experience

We recommend to always perform a test before starting standard production

The product meets the Italian and Ue regulations relating to its proper use.

This document can be subject to variations. Updated versions are available on our website www.siser.it.

For further information, please contact our Sales Office. Thank you.

SISER s.r.l.

V.LE DELLA TECNICA n. 18 – 36100 VICENZA ITALY

TEL. +39 0444 287960 - FAX +39 0444 287959 - E-mail: info@siser.it - www.siser.it

R.E.A. VI 171856 VI – Reg. Imp. VI n. 14971 - Cap. Soc. € 103.300 i.v. – Partita IVA 01591490246

